



*Model ESA-100 - 2.5  
Built in a Movable Desk Enclosure*



*Appropriate for hand-held equipment as used in the flocking industry.  
Perfectly suitable as high-voltage power pack component and insulation testing -  
- High voltage output 0-100 kV DC adjustable  
at load up to 200  $\mu$ A.  
- High voltage output terminal in front or on the backside touch-panel, SPC-able with Accessory board.  
Reliable  
Light Weight  
Simple to use  
Easy Handling*

*The Unit Comprises -  
Designed for a mean output range up to 250 watt High voltage output, adjustable from 0-110 kV.  
Current control - adjustable 0.2 - 2.5 mA DC  
Built-in discharging device for high voltage cable & consumer  
Display of actual high voltage output 0-100 kV and the spray discharge 0-3 mA  
Simple high voltage cable connection with coupling ring screw  
Supply Voltages: 110/230 V AC 50/60 Hz  
High voltage output: 110 kV, max mA DC  
Operative Range and Field of Application -  
Coating and flocking lines  
General electrostatic lines  
Varnishing lines  
Filtering installations  
Enamelling lines*



*Model ESV-100 - 100 kV DC - Hand Held High Voltage Generator Designed for use up to 20 watt  
Small, lightweight (9 kg), portable, electronic high voltage generator used for small spraying equipment.*

## **High Voltage DC Generators**

**Contact WEB Processing to discuss your requirements**

WEB Processing (M/C) Ltd  
New Horwich Road, Whaley Bridge, High Peak. SK23 7LG  
Telephone: 01663 733511, Fax: 01663 734134  
E mail : flock@webprocessing.co.uk  
www.webprocessing.co.uk